



JILONG
Since 1993

OLS-22

Mini Multi-functional
Optical Light Source



Mini size



Network test



Typical output
powder ≥ -5 dBm



LED lighting



Carrier output



特征描述

- ◆ Pocket design, Mini size
- ◆ Support SM/MM/PON three laser output, used in conjunction with OPM
- ◆ Continuous output, three modulation frequencies(270Hz、1kHz、2kHz)
- ◆ Network test, judge signal transmission
- ◆ 2.5mm Universal adaptor for SC/ST/FC
- ◆ With LED lights for dark environment



Selling points



LED lighting

Convenient in dark environment



Network test

Accurate measurement, judge signal transmission
Convenient for carrying and storage, prevent missing.



2.5mm Universal connector



SC



ST



FC



Product Display





Product Specifications

Model	OLS-22
Network test	Interface RJ-45
Wavelength	SM: 1310nm+1550nm MM: 850nm+1300nm PON: 1310nm+1490nm+1550nm
Connector	2.5mm Universal connector
Typical output power	≥-5dBm
Output stability	±0.05dB/ 15mins ±0.1dB/ 8H
Modulation frequencies	CW/ 270Hz /1KHz / 2KHz
LED lighting	Support
Power	AAA 1.5V batteries X 2
Dimension	112 x 57 x 31 mm
Weight	120 g (including batteries)

The above data are obtained in Jilong lab at 20°C temperature