

# KL-6300

## FiberMASTER

## OTDR



- Maximum dynamic range up to 45dB
- 0.8 m event dead zone, 2.5 m attenuation dead zone
- Intelligent link diagram, support Pass & Fail judgment
- iOLA, one-click Intelligent testing of passive PON networks

# FiberMASTER OTDR

The KL-6300 offers superior performance thanks to a completely new algorithm, a large capacity battery and a 7in user-friendly screen. Ensure measurement quality and improve work efficiency, benefits include:

## Full range selection

- Wide dynamic range 30-45dB
- Up to 9 OTDR models for selection
- Five optional modules to be customized

## Operability

- 7-inch color LCD touch screen
- Generate PDF reports quickly
- F/P analytical judgment function
- Smart map to analyze links graphically

## Advanced trace analysis

- Multi-trace analysis
- Bidirectional testing
- 4-points test

## Strong reliability

- Up to 12h battery life
- Minimum sampling resolution 0.04m
- Maximum sampling points 250,000

## Not just OTDR

- VNC/GPS/WIFI
- OPM (Optical power meter module)
- SLS (Stabilized light source module)
- VFL (Visual fault locator module)
- RJ45 (Network Test module)
- FIP (Fiber connector end-face inspection module + analysis function)



\*FIP module can first perform connector end-face detection and then OTDR link testing

# Full range selection

JILONG KL-6300 comes with an iLOA test function that enables complex front-line test work with less-experience, to support a variety of applications, including installation and maintenance (I&M) of mainline fiber (core network, metropolitan area network, mobile forward, mobile backhaul) and troubleshooting of access networks and FTTx. And combines industry-leading OTDR technology with OPM, VFL, SLS, network testing and fiber end inspection capabilities in one powerful handheld device.

## JILONG KL-6300 OTDR Models

Fiber type	Link type		Test application			
SM	Area	PON	Installation (measurement of live fibers and dark fibers)			
			Model/Description		Wavelength(nm) Dynamic range(dB)	
Access network	1x32	KL-6300-S1 (Entry-level model)	1310 32	1550 30		
Acces network / Metropolitan area network	1x64	KL-6300-S2 (basic model)	1310 35	1550 33		
		KL-6300-P1 (3 wavelengths + live model)	1310 32	1550 30	1625 28	
		KL-6300-P2 (High dynamic range wavelengths + live model)	1310 38	1550 36	1625 34	
Metropolitan network / Core network	1x128	KL-6300-S3 (Standard model)	1310 40	1550 38		
		KL-6300-S4 (High dynamic model)	1310 42	1550 40		
		KL-6300-S5 (Super-high dynamic model)	1310 45	1550 43		
MM	LAN	KL-6300-M (MM model)	850 20	1300 22		
		KL-6300-MS (SM&MM model)	850 20	1300 22	+ 1310 32	1550 30

## KL-6300-S1/S2/S3/S4/S5

Dual wavelength module 1310/1550nm,  
used in fiber installations




## KL-6300-M/MS

MM model




# KL-6300-P1/P2

Maintenance models for real-time communication lines



Real-time communication line trace



A trace with a macro bend

## iOLA (Hawkeye)

OTDR faces a series of challenges:




Trace is wrong



Need to analyze several traces



The same work needs to be done twice





Requires complex instrument training



To address these challenges, JILONG has developed a better way to test fiber links: iOLA (Hawkeye) is an OTDR-based application designed to simplify the OTDR testing process by eliminating the need to configure parameters, analyze and interpret multiple complex OTDR curves. It adopts advanced algorithm, can dynamically define the test parameters, and according to the measured network to determine the appropriate curve acquisition times; Multiple pulse widths at multiple wavelengths can also be correlated to locate and identify faults with very high resolution - all at the touch of a button.

## Working principle

Measure the network from the site to an antenna



Short pulse width      Mid pulse width      Long pulse width





Analysis of some events of the measured trace, link the trace together



# Operability

## 7.0 inch multi-touch capacitive touch screen

It supports new gestures to amplification. The screen capture color is clear. The interface design is simple and clear.




## Expand the trace display area

By tapping the icon , you can enlarge the trace display area to view more detail.




## Quickly generate the PDF report

Built -in post -processing software to generate reports of PDF format.




## Pass & Fail analysis function

Automatically perform Pass/Fail judgments for each event based on pre-specified thresholds. The measurement results can be viewed through the result display items (As shown in the red box on the following side).



## Smart map analyze links graphically

With Smart Map, users only need to press one button to execute measurement, detect network events and execute Pass&Fail judgment. It includes a simple icon view that facilitates the location and type of the event, and automatically executes the Pass&Fail judgment of each event based on the pre -specified threshold.




# Advanced trace analysis

The OTDR master module is capable of performing advanced analysis of measured data


## Multi-trace analysis

View multi -trace, can view up to 4 traces at the same time, comprehensive analysis, and the results are more accurate.



## Bidirectional testing

Averaging values obtained from opposite directions provides a more accurate quantification of losses. Bidirectional testing is a great way to improve test integrity in long-distance applications.




## 4-points testing

Real-time monitoring of splicing and insertion loss, less noise impact, more accurate test results.




# Strong reliability

Minimum sampling resolution 0.04m



Maximum sampling points: 250,000



Battery working time: 12 hours




Rubber sheath design: effective shock absorption, anti-fall and anti-bump



# Not just OTDR

## OPM module (built-in)

Used to measure absolute optical power or the relative loss of optical power through a section of fiber link



## VFL module (built-in)

Luminous stability, strong light source, strong penetration; Two light source modes - steady on, flashing



## Fiber connector inspection module (built-in)


The fiber connector end-face inspection module can visualize the surface of the connector, and combine with handle probe(**optional**) can automatically analyze the scratches and dust on the fiber connector, save the surface image and judge the result. And offer a PDF report



\*FIP module can first perform connector end-face detection and then OTDR link testing



## SLS module (built-in)

Output stable continuous signal, used in combination with an OPM to measure optical loss in fiber optic systems



## Network test module (built-in)


Network sequencing + Network ranging + Network hunting (optional)



Fiber connector detection result


## GPS (module optional)

Real-time positioning OTDR position and running track



## WIFI remote control (built-in)


VNC remote control function, using mobile phones or computers online remote operation OTDR easily solve the remote work, can simultaneously take into account multiple room testing, greatly improve efficiency.






# PON optimization


Quickly, easily and correctly measure networks with large losses, such as PON links. In PON mode, simply select the route configuration to be measured on the screen, and OTDR will automatically determine the appropriate measurement conditions and set the optimal value, even after the optical splitter caused large losses, the KL-6300 OTDR can ensure high trace quality.



Set the parameters of the splitter to be measured in PON mode




Ultra-high signal-to-noise ratio measurement



# Additional function


## Self calibration

Shorten maintenance time and reduce maintenance costs




## Power-on password

Acquire and use OTDR by means of leasing, paying in installments according to the agreed time and amount





# Appearance





# OTDR Specifications

## OTDR module

Model	KL-6300-S1	KL-6300-S2	KL-6300-S3	KL-6300-S4	KL-6300-S5	KL-6300-P1	KL-6300-P2	KL-6300-M	KL-6300-MS
Wavelength (nm)	1310/1550	1310/1550	1310/1550	1310/1550	1310/1550	PON 1310/1550/1625 (built-in filter)	850/1300	850/1300+1310/1550	
Dynamic range (dB)	32/30	35/33	40/38	42/40	45/43	32/30/28	38/36/34	20/22	20/22 32/30
Number of optical port	1	1	1	1	1	2	2	1	2
Event dead zone★① (m)	0.8	0.8	0.8	0.8	0.8	1	1	1.5	SM≤1; MM≤1.5
Attenuation dead zone★② (m)	3	3	2.5	2.5	2.5	3	3	5	SM≤3.5; MM≤5
Multi-fiber Measurement				√				√	√
Multi-pulse Measurement				√				✗	√
Splitters Measurement	Max 1:32	Max 1:64		Max 1:128		Max 1:32	Max 1:64	✗	Max 1:32
Applicable fiber					SM (ITU-T G.652)				
Distance range (km)				0.1, 0.3, 0.5, 1.3, 2.5, 5, 10, 20, 40, 80, 120, 160, 260, 320					
Pulse width (ns)				3, 5, 10, 30, 50, 100, 200, 300, 500, 1000, 2500, 5000, 10000, 20000					
Number of sampling points					Max 250000				
Sampling resolution					Min 0.04m				
Distance measurement accuracy				±(0.75 m + Measurement distance × 2 × 10 <sup>-5</sup> + Sampling resolution)					
Loss measurement accuracy				±0.03 dB/dB					
Return loss measurement accuracy				±2 dB					
<b>Optical Power Meter Module</b> (Built-in)					√				
<b>OPM</b>	Wavelength				800 ~ 1650nm				
	Measure range				-70 ~ +6dBm				
	Measure accuracy				< (±0.2dB or ±5%)				
	Display resolution				0.01dB				
	Optical input port				2.5mm Universal ferrule for FC,SC,ST/UPC				
<b>Stabilized Light Source Module</b> (Built-in)					√				
<b>SLS</b>	Wavelength (nm)		1310/1550			1310/1550/1625		850/1300	850/1300+1310/1550
	Output power				≥-10dBm				
	Modulation mode				CW, 270 Hz, 1 kHz, 2 kHz				
	Laser class				Class 1M or Class 1				
	Optical input port				OTDR port				
<b>Visual Fault Locator Module</b> (Built-in)					√				
<b>VFL</b>	Wavelength (nm)				650±10nm				
	Output power				10mW				
	Modulation mode				CW, CHOP (2 Hz)				
	Laser class				Class 3R				
	Optical input port				2.5 mm Universal ferrule type for FC,SC,ST				
<b>Fiber Inspection Probe</b> (Built-in)					Optional				
<b>FIP</b>	Pass / Fail				√				
	Magnification				400X				
	Resolution(um)				≥1.0				
	Electrical interface				USB2.0				
	Optical Connector				FC/UPC,SC/UPC,ST/UPC				
	CMOS size				1/3 inch				
<b>RJ45 Networks Test</b> (Built-in)					√				
<b>RJ45</b>	Applicable cable				CAT5, CAT6				
	Distance of Cable Collation				300m				
	Distance of emitting signal				300m				
<b>GPS Module</b> (Built-in)					Optional				
<b>GPS</b>	Location accuracy				< 50m				
	Real-time Monitoring				support				
<b>WIFI Module</b> (Built-in)					√				
<b>WIFI</b>	Data transmission				√				
	Remote Control				√				



# OTDR Specifications

General Specifications	
Link Map	√
Pass/Fail judgment	√
Distance unit	m, km, mile, kf
PC Analysis Software	√
Languages	English, Español, Chinese, Português, Français, Русский, ภาษาไทย, 한국어
Optical connector	FC/UPC (SC/UPC/APC、LC/UPC/APC、FC/APC Optional)
Display	7-inch touch screen (Resolution: 1024 × 600)
Port	Charge port × 2, 12V - 2.5A & Type C
Operating temperature	-10 ~ 50°C (0 ~ 40°C when AC adapter is being used. 0 to 35°C when battery is be charged)
Storage temperature	-20 to 60°C
Altitude	4000 m
Humidity	0 to 90% RH (20 to 90% with 739874 AC adapter, non-condensing)
Power requirements	100 - 240V AC, 50/60Hz (AC adapter)
Battery	7.4V, 10500mAh, ≥77Wh
LED Light illumination	>15000mcd
Operating time③	12 hours
Data storage	Internal storage: ≥10000 traces, External storage: USB memory
Dimensions	232 mm (W) × 161 mm (H) × 70 mm (D)
Weight	1.6 kg (including internal battery and protectors, excluding OTDR unit and options)

Notes:

★①. Minimum pulse width, return loss: ≥55 dB (≥40 dB for 850/1300 nm), group refractive index: 1.5, the unsaturated peak level <1.5dB.

★②. Minimum pulse width, group refractive index: 1.5, the backscatter level is >0.5dB of the normal level. For SMF, at 1310nm, return loss: ≥55dB. For MMF, at 850nm, return loss: ≥40dB.

★③. New Battery

All specifications valid at 23°C ± 2°C (73.4°F ± 3.6°F) unless otherwise specified.